

AMENDMENTS TO THE SPECIFICATION

Please amend paragraph [0018] (page, lines 8-9) as follows:

[0018] FIGURES 2A and B depicts ~~an~~ exemplary embodiments of an assembled portion of the device of FIGURE 1, having vented and open-mold configurations, respectively.

Please amend paragraph [0042] (page 10, lines 12-20) as follows:

[0042] As mentioned, preferably, ear mold 11 is at least partially hollow on the inside. Accordingly, in one embodiment, ear mold 11 may receive internally one or more other elements of device 40. In some embodiments, at least a portion of speaker fastener 14, along with speaker 13, which may be partially disposed therein, are passed through opening 18 in receiving member 12 and into ear mold 11 (e.g., the assembled portion of device 40 shown in FIGURE 2A and 2B). Similar to earlier discussions, in a preferred embodiment, speaker 13 and/or speaker fastener 14 are of a particular size and shape such that when speaker 13 and/or speaker fastener 14 are coupled to ear mold 11, the assembly of ear mold 11, speaker 13, and/or speaker fastener 14 may be placed so deep into a user's ear canal as to touch the bony portion of the user's ear canal. FIGURE 2A shows completely-in-canal unit 10 with vents 25, while FIGURE 2B shows an open mold configuration of completely-in-canal unit 10 having open area 26.